

Display Device

BACview⁵

Locally access a control module to easily view and modify pertinent data with the easy-to-use BACview⁵ keypad/display. It simply plugs into an Rnet connection and allows you to display and modify user-defined properties without any computer software. The BACview⁵ features menu direction buttons and a 2-line by 16-character backlit LCD display for easy reading even in poor lighting conditions. The device also includes an alarm indicator light.



Key Features and Benefits

- Compatible with I/O Zone, I/O Flex, and I/O Pro Controllers.
- Flexible design allows panel or wall mounting; can be located up to 500 feet from the control panel.
- Can share Rnet (OEMCtrl sensor network) with up to 5 Room Sensors.
- Backlit LCD display enhances reading even in poor lighting conditions.
- Allows customization of building properties for each project using industry-standard HTML.
- Password protection provides security.

Specifications

Power	Supplied by the 4 conductor cable (+12Vdc @ 250mA).
Physical	Rugged aluminum enclosure for protection and easy backplane mounting.
Operating Range	32° to 130°F (0° to 54.4°C), 10%-90% RH non-condensing.
Backlit LCD Display	2-line by 16-character display.
Hardware Compatibility	All controllers with Rnet capability.
Status Indication	HTML programmable 2-line by 16-character back lit LCD display with alarm LED indicator.
Protection	Provides 15KVESD protection to the enclosure.
Listed by	UL 916 (PAZX), CE (1997), FCC Part 15 - Subpart B - Class A.
Weight	0.6 lbs. (.27 Kg)
Mounting	Wall or panel mounting; remote mounting up to 500 feet. Standard J box may be used.
Overall Dimensions	5 3/8" (width) by 4 7/16" (height) by 1" (recommended panel depth). 136.5mm (width) by 112.7mm (height) by 25.4mm (recommended panel depth).